

AB PROFIT HOGA AUR BHI ZYAADA



FE
Series

1112 LPT

BS6 P2
Phase 2 Ready

Safer
 Smarter
 Greener
 Better Fuel Efficiency
 Lower Total Cost of Ownership

TATA TRUCKS
DESH KE TRUCKS

Technical Specifications

Models	1112 LPT DCR 125B6PH2M5							
Engine	4SPCR BS VI Ph2							
Engine Type	4 Cylinder in line water cooled direct Injection diesel engine with intercooler							
Engine Displacement	2 956 cc							
Power	74.5 kW (100 Ps) Light Mode / 92 kW Heavy Mode (125 Ps) @ 2 800 r/min							
Torque	300 Nm @ 1 000 - 2 200 r/min (Light Mode), 360 Nm @ 1 400 - 1 800 r/min (Heavy Mode)							
Clutch	Single plate dry friction type - 310 mm dia (with Booster)							
Gearbox	G550, 5 Speed, MK2 Manual Synchromesh Gearbox (5F, 1R)							
Gear Box Ratio	1st - 8.07, 2nd - 4.76, 3rd - 2.75, 4th - 1.66, 5th - 1.00, Rev - 7.48							
Suspension - Front Type	Parabolic leaf spring with Hydraulic Double acting Telescopic Shock Absorbers							
Suspension - Rear Type	Semi elliptical Leaf spring,							
Tyres	8.25 R16 - 16PR Low CRR Tyre (Front - 2 / Rear-4)							
Cabin Type	New Gen LPT Walk Through Day Cabin							
Steering Type*	Tilt & Telescopic Power Steering (Dia 420 mm) 4 Spoke							
Brakes Type	Dual Circuit Full Air S" Cam Brakes With Auto Slack Adjuster (Drum - Drum) - 325 mm							
Ground Clearance	214 mm							
Gradeability	22.90 %							
Rear Axle	Banjo Type - Single reduction htpoid gears, fully floating axle shafts - RAR: 4.85							
Battery	12V, 100 Ah							
Fuel Tank Capacity	120 L HD Polimer Fuel Tank							
Load Body Variants	CAB & HSD							
GVW	11 450 kg							
FAW	4 000 kg							
RAW	7 450 kg							
Long member Size (Lx B x H)	200 mm x 60 mm x 5 mm							
Wheelbase	3 550 mm	3 920 mm	4 530 mm	4 920 mm				
TCD	12 500 mm	13 800 mm	16 100 mm	17 500 mm				
Variants	CAB	HSD	CAB	HSD	CAB	HSD	CAB	HSD
Load Body Dimensions (L x W x H)	NA	4 347 mm x 2 260 mm x 2 090 mm	NA	5 340 mm x 2 260 mm x 2 090 mm	NA	6 290 mm x 2 260 mm x 2 090 mm	NA	6 915 mm x 2 260 mm x 2 090 mm
Warranty	3 years / 3 00 000 km							
Seating Capacity	D + 2							
DEF Tank Size	18 l							
FIP Model	Delphi CR System (1 800 + bar pressure)							
Service Interval	40 000 km or 1 Year. Hub Greasing 1 20 000 km, Gear Oil Change Interval - 2 40 000 km							

Key Features & Benefits

Gear Shift Advisor
 2 200 mm Wide Cabin
 Dual Mode FE Switch Light & Heavy

THU Bearing
 Low CRR Tyre
 Fleetedge Telematics

Applications

Cement, Building Construction
 Parcel & Courier E Commerce
 Pharma
 Fruits & Vegetables
 FMCG

LPG Cylinder
 Food grains
 Industrial Goods
 Containers & Reefers
 White Goods



TATA MOTORS

To know more, visit your nearest Tata Motors dealership

www.light-trucks.tatamotors.com

18 00 20 97 979 Follow us on