

Technical Specifications

Model	SFC 407 GOLD DCR33HSD 100B6M5	
Engine	4 SP BS6 Phase 2 TCICengine	
Engine Type	4 Cylinder In line Water Cooled Direct Engine water cooled with Intercooler	
Engine Displacement	2 956 cc	
Power	74.5 kW (100 PS) @ 2 800 r/min	
Torque	300 Nm @ 1000 - 2 200 r/min	
Clutch	Single Plate Dry Friction type - 280 mm dia	
Gearbox	G 440 (5F,1R) Cable Shift Mechanism	
Suspension- Front Type	Parabolic Suspension	
Suspension- Rear Type	Semi-Elliptical Leaf Spring	
Tyres	7.50 R 16-16 PR	
Cabin Type	2.1 m SFC cabin	
Steering Type	Power Steering	
Brakes	H2LS Hydraulic Drum Brakes	
Ground Clearance	190 mm	
Gradeability	37 %	
Battery	12 V, 100 Ah	
Fuel Tank Capacity	60 l	
Load Body Variants	CBC, HSD	
GVW	4 995 kg	
Kerb Weight HSD	2 620 kg	
Wheelbase	3 305 mm	
TCO	14 m	
Load Body Dimensions (LxWxH)	3 070 mm x 1 962 mm x 1 835 mm	
Warranty	3year or 3 00 000 km	

Load Body Dimensions			
Cabin Type	Day Cabin		
Wheelbase	3 305 mm	3 550 mm	
Length	3 070 mm	3 690 mm	
Width	1962 mm		
Height	1835 mm		

Key Features & Benefits









7.50 R16 Radial Tyre

Available in 10 ft (3 048 mm) &12 ft (3 658 mm) deck options

Applications

4.95 T





Fruits & Vegetables

Market Load

FMCG

White Goods









Parcel Courier & E Commerce

Industrial Goods

Food Grains

LPG Cylinder





TATA MOTORS

To know more, visit your nearest Tata Motors dealership







